



HUSQVARNA 125BVx

An efficient handheld leaf blower that combines high blowing power with user friendliness making it the perfect petrol blower and garden vacuum for home owners. The Husqvarna 125BVx comes with both round and flat nozzle attachments. The round nozzle attachment allows for a broader airstream for clearing wider areas, whilst a flat nozzle attachment increases airstream and directional accuracy when required. This petrol leaf blower is easy to start thanks to its Smart Start® technology and is well balanced and easy to manoeuvre thanks to its in-lined air outlet. A Vac kit is included with the Husqvarna 125BVx to transform your petrol leaf blower into a garden blower vac for added versatility.



Quick Start with Air Purge

Air purge removes air from carburetor and fuel system for easy starting




Multi-Speed Control

Variable speed throttle with cruise control option for easier handling

Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.



Adjustable Tube Length

Easily adjust the blowing tube length for maximum performance



FEATURES

- Stop switch automatically resets to ON so trimmer is ready for next use
 - Variable speed throttle with cruise control option for easier handling
 - Air purge removes air from carburetor and fuel system for easy starting
- Easily adjust the blowing tube length for maximum performance
 - 470 CFM for maximum blowing performance
 - Balanced for less strain on your arms, shoulders and back
 - Turn the blower into a mulching lawn vacuum to easily break down and collect debris

Technical Specifications	
CAPACITY	
Air flow in housing	13.31 m³/min
Air flow in pipe	12.03 m³/min
Air speed	76 m/s
Air speed (flat nozzle)	76 m/s
Air speed (round nozzle)	58.12 m/s
Blow speed	273 km/h
Blowing Force	12.5 N
Idling speed	3000 rpm
Maximum power speed	8000 rpm
Max engine/motor	10000 rpm
Power output	0.8 kW
Vac bag capacity	64.35 l
CERTIFICATIONS	
Cert machine dir. 2006/42/EC Decl. No.	YES
Commercial Warranty	90 Days
Homeowner Warranty	2 Years
DIMENSIONS	
Article gross weight	8000 g
Article net weight	4000 g
Tube diameter	65.0 mm
Tube length	641.0 mm
Weight	4.35 kg
ENGINE	
Carburetor	Zama C1Q
Cylinder bore	35 mm
Cylinder displacement	28 cm³
Cylinder stroke	28.7 mm
Electrode gap	0.6 mm
Engine Family CARB	*PWES.0284BQ
Engine Family EPA	*PWES.0284BQ
Fuel tank volume	0.5 l
Fuel consumption	575 g/kWh
Idling speed	3000 rpm
Maximum power speed	8000 rpm
Power output	0.8 kW
Spark plug	Champion RCJ6Y
EQUIPMENT	
Harness	Single harness
Nozzle type	Round+ Flat
Vacuum Kit	Yes
LUBRICANTS	
Fuel consumption	575 g/kWh
Fuel tank volume	0.5 l
Lubricant type (Engine)	Husqvarna 2 stroke or equiv. at 50:1
Power/fuel type	Petrol
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper	0 g
Paper + Cardboard total	1080 g
PE total	8 g
PET total	0 g
Plastic foil	8 g
Plastic rigid	0 g
Plastic total	8 g
PS/EPS/HIPS total	0 g
PACKAGING	
Packaging height	480 mm
Packaging length	530 mm
Packaging volume	71.232 dm³
Packaging width	280 mm
Pallet layers	2
Quantity in Master pack	1
EMISSION DATA	
Exhaust emissions (CO average)	138 g/kWh
Exhaust emissions (CO average)	168 g/kWh

Technical Specifications	
Exhaust emissions (CO FEL)	536 g/kWh
Exhaust emissions (CO average)	1457 g/kWh
Exhaust emissions (CO2 EU V)	1392 g/kWh
Exhaust emissions (HC average)	28 g/kWh
Exhaust emissions (HC average)	41.5 g/kWh
Exhaust emissions (NOx average)	1 g/kWh
Exhaust emissions (NOx average)	0.4 g/kWh
EMISSION DATA CARB	
Engine Family CARB	*PWES.0284BQ
EMISSION DATA EPA	
Exhaust emissions (CO average)	168 g/kWh
Exhaust emissions (CO FEL)	536 g/kWh
Exhaust emissions (HC average)	41.5 g/kWh
Exhaust emissions (NOx average)	0.4 g/kWh
EMISSION DATA EU	
Exhaust emissions (CO average)	138 g/kWh
Exhaust emissions (CO average)	1457 g/kWh
Exhaust emissions (HC average)	28 g/kWh
Exhaust emissions (NOx average)	1 g/kWh
SOUND AND NOISE	
Sound level	112 dB(A)
Sound power level, guaranteed (LWA)	112 dB(A)
Sound power level, measured	109 dB(A)
Sound pressure (15m)	70 dB(A)
Sound pressure level at operators ear	94 dB(A)
VIBRATION	
Equivalent vibration level (ahv, eq) handle	11.1 m/s ²