



Husqvarna TC242T

Husqvarna TC 242 T is a powerful tractor, developed for use in medium- to large-sized gardens. Equipped with integrated 320 L rear collector, pedal-operated, hydrostatic transmission and low vibe deck drive.



Sliding, angled seat

Adjustable while seated; seat moves forward and down, or backwards and up.



Reinforced Cutting Deck

The stamped cutting deck is reinforced with heavy flat-stock steel for added strength and durability on the leading edge and trim side. (48" shown)

Pedal-operated hydrostatic transmission

Easy speed and direction control with pedal-operated hydrostatic transmission. Separate pedals for forward and reverse.



Superior Quality Cut

Air Induction™ mowing technology lifts grass up straight for a higher-quality cut



FEATURES

- Speed and direction are controlled by pedals, letting you keep both hands on the steering wheel
- Reinforced Cutting Deck
- Adjustable seat, while seated
- Air Induction™ mowing technology lifts grass up straight for a higher-quality cut
- Oversized steering wheel for less steering effort
- Cast front axle for superior stability
- Hour meter with service minder
- Solid steel hood
- Rugged frame
- Reduces the risk of scalping uneven lawns
- Easy to get operating with automatic choke.
- Easy to get operating with automatic choke.
- Speed and direction are controlled by pedals, letting you keep both hands on the steering wheel
- Hour meter with service minder
- Reinforced Cutting Deck
- Solid steel hood
- Cast front axle for superior stability
- Adjustable seat, while seated
- Rugged frame
- Air Induction™ mowing technology lifts grass up straight for a higher-quality cut
- Manual blade engagement
- Air Induction™ mowing technology lifts grass up straight for a higher-quality cut
- Oversized steering wheel for less steering effort
- Heavy duty frame for rough use
- Reduces the risk of scalping uneven lawns
- Oversized steering wheel for less steering effort

Technical Specifications	
BATTERY	
Battery voltage	12 V
CAPACITY	
Net power at preset rpm	2600 rpm
Power output	9.6 kW
Turning radius, min	16 in
Uncut circle	152 cm
DIMENSIONS	
Article gross weight	358338 g
Article net weight	287124 g
Base machine, height	127 cm
Base machine, length	240 cm
Base machine, width (chute down)	110 cm
Base machine, width (chute up)	110 cm
Base machine, width	110 cm
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Central, spring-assisted
Cutting height steps	6
Cutting width	108 cm
Seat back height	High 15"
Tyre dimensions, front	15X6-6
Tyre dimensions, rear	18X8.5-8
Weight	287 kg
Wheelbase	122 cm
ENGINE	
Cylinders	2
Cylinder displacement	656 cm ³
Engine cooling	Air
Engine name	Intek
Fuel tank volume	9.5 l
Fuel tank volume	2.5 gal (US)
Generator	3.5 A
Motor/engine manufacturer	Briggs & Stratton
Transmission manufacturer	Tuff Torq
Transmission model	K46
Transmission type	Hydrostatic
EQUIPMENT	
Air filter type	Auto-type Paper
Anti-scalp wheels	2
BioClip® kit	Available as accessory
Blade engagement	Manual
Blade type	High Performance
Blades	2 pcs
Collector	Included
Cup holder	Yes
Cutting deck type	Stamped, Reinforced
Cutting methods	Collect/Mulch
Deck Wash Port	Yes
Drive method	Pedal-operated
Front-End Protection	Available as accessory

Technical Specifications	
Generator	3,5 A
Headlights	Yes
Hour meter type	Digital with pre-programmed service intervals
Powder-coated cutting deck	Yes
Seat type	High back 15" (armrest as accessory)
LUBRICANTS	
Engine lubrication type	Full pressure with oil filter
Fuel consumption	405 g/kWh
Fuel tank location	Front
Oil capacity	1.9 l
Oil filter	Yes
Power/fuel type	Petrol
MATERIALS	
Cutting deck material	Steel
Master pack: Paper + Cardboard	530 g
Metal total	0 g
Paper + Cardboard total	4681 g
PE total	650 g
PET total	0 g
Plastic foil	465 g
Plastic rigid	200 g
Plastic total	665 g
PS/EPS/HIPS total	0 g
Seat material	Vinyl
PACKAGING	
Packaging height	1245 mm
Packaging length	2261 mm
Packaging volume	3171.13 dm ³
Packaging width	1168 mm
Quantity in Master pack	1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	100.0 dB(A)
Sound pressure level at operators ear	84 dB(A)
VIBRATION	
Vibration level seat	0.73 m/s ²
Vibration level steering wheel	3.41 m/s ²

ACCESSORIES



FRONT MOUNTED ROTARY
BROOM
544 92 16-01



TRO038 - SNOW FRONT BLADE
122CM
544 92 17-01



AERATOR
586 63 69-01




TRO057 - COUNTERWEIGHT CT
580 38 97-01



SWEEPER
582 71 99-01



SWEEPER
586 63 65-01



MOSS RAKE
586 63 66-01



DETHATCHER
586 63 68-01



ATTACHMENT PLATFORM
586 63 72-01



HUSQVARNA PLUG AERATOR
588 21 27-01



GRAVEL HARROW
953 51 24-01



TRO060 - MULCH PLUG
960 71 00-38



DEFLECTOR
960 71 00-41



TRO034 - SNOW CHAINS WITH
WELDED SPIKES
964 99 43-01



TRO006 - ROLLER
965 89 94-01



TRAILER 275
501 00 82-01



TRACTOR BRUSH GUARD.
505 56 88-13

TRACTOR COVER - LARGE
505 63 08-82



LOADING RAMPS
505 69 90-43



SPREADER 75
967 02 72-01



LOADING RAMPS
505 69 90-41



TRO062 - BUMPER
954 12 00-49



LOADING RAMPS
505 69 90-40