



Husqvarna 122HD60

The Husqvarna 122HD60 is a compact and lightweight petrol hedge trimmer for domestic use, with easy to use functions such as Smart Start®, and the benefit of a low noise engine. With an adjustable rear handle this small hedge trimmer with 59cm blade makes easy work of cutting sides and tops of hedges.



LowVib® Technology

Dampeners between the engine and chassis significantly reduce vibrations so you can work more comfortably



Smart Start® Technology

Specially-designed engine and starter for easy and fast starting with minimum effort

Low Noise Engine

Specially-designed engine reduces extra noise



Adjustable Rear Handle

Multiple handle positions makes hedge cutting easy and comfortable



FEATURES

- Specially-designed engine reduces extra noise
- Specially-designed engine and starter for easy and fast starting with minimum effort
- Dampeners between the engine and chassis significantly reduce vibrations so you can work more comfortably
- Multiple handle positions makes hedge cutting easy and comfortable
- Extend your reach for more comfortable use
- Stop switch automatically resets to ON so trimmer is ready for next use
- Air purge removes air from carburetor and fuel system for easy starting

Technical Specifications		
CAPACITY		
Clutch engagement speed (±120)		4300 rpm
Cutting speed		4050 cut/min
Idling speed		2800 rpm
Knife adjustment range, up/down Down		0 °
Knife adjustment range, up/down Up		0 °
Max engine/motor		9000 rpm
Maximum power speed		7800 rpm
Power output		0.6 kW
Teeth opening		28 mm
Torque, max.		0.8 Nm
Torque, max. at rpm		6000 rpm
CERTIFICATIONS		
Cert machine dir. 2006/42/EC Decl. No.		SEC/10/2280
DIMENSIONS		
Article gross weight		8000 g
Article net weight		6030 g
Knife length		59 cm
Recommended maximum twig diameter		20 mm
Weight		4.9 kg
Weight (excl. cutting equipment)		4.9 kg
ENGINE		
Carburetor		Ruixing
Cylinder bore		32 mm
Cylinder displacement		21.7 cm³
Cylinder stroke		27 mm
Electrode gap		0.5 mm
Engine Family CARB		LHVXS.0224EB
Engine Family EPA		MHVXS.0224EB
Gear ratio		4.44
Ignition module air gap		0.3 mm
Max engine/motor		9000 rpm
Spark plug		Husqvarna HQT-4 672201
EQUIPMENT		
Air filter type		Foam
Connectivity		Not applicable
LUBRICANTS		
Fuel consumption		575 g/kWh
Fuel tank volume		0.3 l
Lubricant type (Engine)		Husqvarna 2 stroke or equiv. at 50:1
Power/fuel type		Gasoline
MATERIALS		
Master pack: Paper + Cardboard		0 g
Metal total		0 g
Other plastic: rigid		64
Paper		3800 g
Paper + Cardboard total		5870 g
PE total		0 g
PET total		0 g
Plastic foil		10 g
Plastic rigid		64 g
Plastic total		74 g
PS/EPS/HIPS total		0 g
PACKAGING		
Packaging height		282 mm
Packaging length		1210 mm
Packaging volume		78.5 dm³
Packaging width		230 mm
Pallet layers		6
Quantity in Master pack		1
EMISSION DATA CARB		
Engine Family EPA		MHVXS.0224EB
Engine Family CARB		LHVXS.0224EB
Exhaust emissions (CO average)		254.87 g/kWh
Exhaust emissions (CO average)		1543 g/kWh

Technical Specifications	
Exhaust emissions (HC average)	42.02 g/kWh
Exhaust emissions (NOx average)	0.46 g/kWh
EMISSION DATA EPA	
Exhaust emissions (CO average)	254.87 g/kWh
Exhaust emissions (CO FEL)	536 g/kWh
Exhaust emissions (CO average)	1543 g/kWh
Exhaust emissions (HC average)	42.02 g/kWh
Exhaust emissions (NOx average)	0.46 g/kWh
EMISSION DATA EU	
Exhaust emissions (CO average)	230.89 g/kWh
Exhaust emissions (CO average)	1528 g/kWh
Exhaust emissions (CO2 EU V)	1528 g/kWh
Exhaust emissions (HC average)	42.55 g/kWh
Exhaust emissions (NOx average)	0.37 g/kWh
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	101 dB(A)
Sound power level, measured	100 dB(A)
Sound pressure level at operators ear	94 dB(A)
VIBRATION	
Daily Vibration (Aeqv)	4.1 m/s ²
Daily Vibration Exposure (A8)	2.71 m/s ²
Daily Vibration Time (Time factor)	3.5 h
Equivalent vibration level (ahv, eq) front handle	4.1 m/s ²
Equivalent vibration level (ahv, eq) rear handle	3.6 m/s ²