




HUSQVARNA 525RJX

Efficient and easy to use brushcutter with J handle that allows you to use both trimmer line and grass blade. Has the lowest vibration rates in its class.



Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.



J-handle

Equipped with J-handle for greater versatility.

Intuitive controls

Easy to use and maneuver



X-Torq® engine

The X-Torq® engine design increases torque over a wider rpm range providing maximum cutting power.



FEATURES

- Easy to use and maneuver
- J-handle for increased versatility
- Stop switch automatically resets to ON so trimmer is ready for next use
- Powerful 50cc X-TORQ® engine reduces emissions by up to 60% and increases fuel efficiency by up to 20%
- Standard harness for lighter brushcutters
- Air purge removes air from carburetor and fuel system for easy starting
- Tap 'n' Go trimmer head is easy to use and refill
- Specially-designed engine and starter for easy and fast starting with minimum effort
- Versatile use with combi guard
- Comfortable handles
- Grass bevel gear for best cutting performance

Technical Specifications	
CAPACITY	
Clutch engagement speed (±120)	4000 rpm
Idling speed	3000 rpm
Maximum power speed	8500 rpm
Maximum rpm output shaft	6500 rpm
Power output	1 kW
Torque, max.	1.2 Nm
Torque, max. at rpm	6000 rpm
DIMENSIONS	
Article gross weight	7218 g
Article net weight	7218 g
Cutting width	45 cm
Tube diameter	24 mm
Tube length	1483 mm
Weight (excl. cutting equipment)	4.3 kg
ENGINE	
Cylinder bore	34 mm
Cylinder displacement	25.4 cm³
Cylinder stroke	28 mm
Electrode gap	0.65 mm
Gear ratio	13
Ignition module air gap	0.3 mm
Spark plug	NGK BPMR8Y
EQUIPMENT	
Drive gear angle	30 °
Grass blade	Grass 255–4
Harness	Single harness
Trimmer head	T35 M10
LUBRICANT	
Fuel consumption	600 g/kWh
Fuel tank volume	0.51 l
Lubricant type (Engine)	Husqvarna 2 stroke or equiv. at 50:1
Power/fuel type	Gasoline
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Other plastic: rigid	400 g
Paper	10000 g
Paper + Cardboard total	10000 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	400 g
Plastic total	400 g
PS/EPS/HIPS total	0 g
Wood/Nature pac	20000 g
PACKAGING	
Packaging height	280 mm
Packaging length	1850 mm
Packaging volume	150.22 dm³
Packaging width	290 mm
Quantity in Master pack	1
EMISSION DATA EU	
Exhaust emissions (CO average)	87.57 g/kWh
Exhaust emissions (CO2 EU V)	1141 g/kWh
Exhaust emissions (NOx average)	0.56 g/kWh
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	106 dB(A)
Sound power level, measured	104 dB(A)
Sound pressure level at operators ear	94 dB(A)
VIBRATION	
Equivalent vibration level (ahv, eq) front handle	2.1 m/s²

Technical Specifications

Equivalent vibration level (ahv, eq) rear handle

1.9 m/s²