




## HUSQVARNA 525BX

Powerful and well-balanced handheld blower for professional use. The patented X-Torq® engine technology in combination with the special fan and housing design means high blowing capacity that is easy to control. The anti-vibration system Low Vib makes work less strenuous – even during long shifts. And all intuitive controls, i.e. Cruise Control, contribute to efficient and convenient operation at all times.



### Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.



### Adjustable Tube Length

Easily adjust the blowing tube length for maximum performance

### X-Torq® engine

The X-Torq® engine design increases torque over a wider rpm range providing maximum cutting power.



### Quick Start with Air Purge

Air purge removes air from carburetor and fuel system for easy starting



## FEATURES

- Powerful 50cc X-TORQ® engine reduces emissions by up to 60% and increases fuel efficiency by up to 20%
- Easily adjust the blowing tube length for maximum performance
- Stop switch automatically resets to ON so trimmer is ready for next use
- Air purge removes air from carburetor and fuel system for easy starting
- Variable speed throttle with cruise control option for easier handling
- Easy to operate with in lined air outlet

Technical Specifications	
CAPACITY	
Air flow in housing	14 m³/min
Air flow in pipe	13 m³/min
Air speed (flat nozzle)	86 m/s
Air speed (round nozzle)	70 m/s
Blowing Force	15 N
Idling speed	3000 rpm
Maximum power speed	7300 rpm
Power output	0.9 kW
Torque, max.	1.15 Nm
Torque, max. at rpm	6000 rpm
DIMENSIONS	
Article gross weight	7660 g
Article net weight	6500 g
Tube diameter	68 mm
Tube length	550 mm
Weight	4.4 kg
ENGINE	
Cylinder bore	34 mm
Cylinder displacement	25.4 cm³
Cylinder stroke	28 mm
Electrode gap	0.65 mm
Engine Family CARB	FHQZS.0254GQ
Engine Family EPA	FHQZS.0254GQ
Fuel tank volume	0.45 l
Fuel consumption	518 g/kWh
Idling speed	3000 rpm
Ignition module air gap	0.3 mm
Maximum power speed	7300 rpm
Power output	0.9 kW
Spark plug	NGK BPMR8Y
EQUIPMENT	
Nozzle type	Round+ Flat
Vacuum Kit	No
LUBRICANTS	
Fuel consumption	518 g/kWh
Fuel tank volume	0.45 l
Lubricant type (Engine)	Husqvarna 2 stroke or equiv. at 50:1
Power/fuel type	Petrol
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper	131 g
Paper + Cardboard total	131 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
PACKAGING	
Packaging height	400 mm
Packaging length	460 mm
Packaging volume	71.76 dm³
Packaging width	390 mm
Pallet layers	5
Quantity in Master pack	1
EMISSION DATA	
Exhaust emissions (CO average)	379.85 g/kWh
Exhaust emissions (CO average)	988 g/kWh
Exhaust emissions (CO2 EU V)	1110 g/kWh
Exhaust emissions (HC average)	25.99 g/kWh
Exhaust emissions (NOx average)	0.29 g/kWh
EMISSION DATA CARB	
Engine Family CARB	FHQZS.0254GQ
EMISSION DATA EU	
Exhaust emissions (CO average)	379.85 g/kWh

Technical Specifications	
Exhaust emissions (CO average)	988 g/kWh
Exhaust emissions (HC average)	25.99 g/kWh
Exhaust emissions (NOx average)	0.29 g/kWh
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	106 dB(A)
Sound power level, measured	104 dB(A)
Sound pressure level at operators ear	91 dB(A)
VIBRATION	
Daily Vibration (Aeqv)	1.2 m/s²
Daily Vibration Exposure (A8)	0.5 m/s²
Daily Vibration Time (Time factor)	1.5 h
Equivalent vibration level (ahv, eq) handle	1.2 m/s²