



Husqvarna PW 350

A truly high performing machine with robust and purposeful design, for excellent results and demanding jobs such as vehicles and stone walls. The Low Force grip activates the trigger with less effort and more comfort. The induction motor and the metal pump ensure a dependable performance and long product lifetime. Transportation is easy thanks to the aluminum carrying handle. Quick hose coupling, large and robust wheels for better traction, and a long spray lance add to the experience. Two swivel functions, for nozzle adjustment and quick connection, prevent hassle. On-board accessory storage, hose reel and power cord storage make operation efficient. Two nozzles and one foam sprayer are included.



Induction Motor

Highly durable induction motor has high performance and long life.



Hose reel

Convenient and efficient storage of hose with easy roll-up.


Low Force Grip

In this ergonomically designed function, the trigger's activation is perfectly adjusted to your fingers. This means less effort and more comfort for your hand, especially during prolonged use.



Metal Pump

The pump is made of metal to minimise the risk of breakage and to give your product a long lifetime.



FEATURES

- Less effort and more comfort for your hand
 - Hose reel with supporting guide
 - High durability and long service life
 - Gives the product a long lifetime
 - Easy movement and reliable traction
 - Easy transportation and convenient storage
 - Comfort and non-tangling hose
 - Saves time and prevents tangling
- Maximizes efficiency and comfort
 - Makes moving and transport of the machine extra convenient
 - Easy to see the remaining level of detergent and amount used
 - More ergonomic working positions
 - Increased versatility for a wide range of cleaning tasks
 - Targeted high cleaning performance
 - Easy access and more efficient work

Technical Specifications	
CAPACITY	
Container capacity	0.5 l
Electric protection class	IP X5
Max pressure	150 bar
Max self-priming suction	1 m
Max. Water inlet temperature	40 °C
Operating pressure Max	135 bar
Water flow	420–500 l/h
DIMENSIONS	
Article gross weight	18800 g
Article net weight	18800 g
Hose length	9 m
Length of cord	5 m
ENGINE	
Electric protection class	IP X5
Frequency	50 Hz
Phases	1 ph
Power rating	2100 W
Rated current	9.5 A
Voltage	230 V
EQUIPMENT	
Plug	Type G - 230 V
MATERIALS	
Cardboard	2799.5 g
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper	144.5 g
Paper + Cardboard total	2944 g
PE total	137 g
PET total	0 g
Plastic foil	137 g
Plastic rigid	0 g
Plastic total	137 g
PS/EPS/HIPS total	0 g
PACKAGING	
Packaging height	780 mm
Packaging length	375 mm
Packaging volume	114.08 dm³
Packaging width	390 mm
Quantity in Master pack	1
Units Per Pallet	6 pcs
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	90 dB(A)