




HUSQVARNA 135 Mark II

Lightweight, versatile and easy to use. This petrol chainsaw is powerful enough for tasks around the garden and features an X-Torq® engine to reduce emissions. It starts quickly and is easy to handle and maintain. It features an inertia chain brake for extra safety, while the chain is easily adjusted using the side-mounted chain tensioner. This Husqvarna petrol chainsaw is ideal for occasional cutting tasks such as cutting firewood and felling small trees.



Air Injection™

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



Powerful and Efficient X-TORQ® Engine

Powerful X-TORQ® engine reduces emissions by up to 60% and increases fuel efficiency by up to 20%

Chain tensioning from the side

Allows quick and convenient chain tensioning.



Inertia chain brake

Effective inertia-activated chain brake.



FEATURES

- Quickly and easily adjust the chain
- Powerful X-TORQ® engine reduces emissions by up to 60% and increases fuel efficiency by up to 20%
- Less filter cleanings with Air Injection®
- Reduces the likelihood of injury due to kickback
- Provides easier starting and reduces the risk of engine flooding
- Air purge removes air from carburetor and fuel system for easy starting
- Dampeners between the engine and chassis significantly reduce vibrations so you can work more comfortably
- Specially-designed engine and starter for easy and fast starting with minimum effort

Technical Specifications	
CAPACITY	
Chain speed at 133% of maximum engine power speed	22.3 m/s
Chain speed at max power	16.8 m/s
Clutch engagement speed (±120)	4000 rpm
Clutch engagement upper limit	4500 rpm
Idling speed	3000 rpm
Idling upper limit	3200 rpm
Ignition module air gap	0.3 mm
Maximum power speed	9000 rpm
Power output	1.6 kW
Racing speed lower limit	11200 rpm
Torque, max.	1.84 Nm
Torque, max. at rpm	8000 rpm
CERTIFICATIONS	
Cert machine dir. 2006/42/EC Decl. No.	Yes
DIMENSIONS	
Article gross weight	7300 g
Article net weight	6000 g
Bar length (inch)	14 in
Bar length	35 cm
Weight (excl. cutting equipment)	4.7 kg
ENGINE	
Cylinder bore	39 mm
Cylinder displacement	38 cm ³
Cylinder stroke	32 mm
Electrode gap	0.55 mm
Engine Family CARB	*PWES.0384CX
Engine Family EPA	-PWES.0384CX
Ignition module air gap	0.3 mm
Spark plug	NGK BPMR7A
EQUIPMENT	
Bar mount type	HSM
Chain type	S93G
Chainsaw sub-group	Occasional use chainsaws
Handle type	Standard
Pitch	3/8" mini
Sprocket type	Spur 6
LUBRICANT	
Fuel consumption	725 g/kWh
Fuel consumption	0.725 kg/h
Fuel tank volume	0.37 l
Lubricant type (Engine)	Husqvarna 2 stroke or equiv. at 50:1
Oil pump type	Automatic
Oil tank volume	0.26 l
Power/fuel type	Gasoline
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper	34 g
Paper + Cardboard total	874 g
PE total	0 g
PET total	0 g
Plastic foil	12 g
Plastic rigid	0 g
Plastic total	12 g
PS/EPS/HIPS total	0 g
PACKAGING	
Packaging height	333 mm
Packaging length	495 mm
Packaging volume	27.814 dm ³
Packaging width	285 mm
Quantity in Master pack	1
EMISSION DATA CARB	
Engine Family CARB	*PWES.0384CX
Exhaust emissions (CO average)	330.7 g/kWh

Technical Specifications	
Exhaust emissions (CO average)	877 g/kWh
Exhaust emissions (HC average)	40.85 g/kWh
Exhaust emissions (NOx average)	1.14 g/kWh
EMISSION DATA EPA	
Engine Family EPA	-PWES.0384CX
Exhaust emissions (CO average)	331 g/kWh
Exhaust emissions (CO FEL)	536 g/kWh
Exhaust emissions (CO average)	877 g/kWh
Exhaust emissions (HC average)	40.85 g/kWh
Exhaust emissions (NOx average)	1.14 g/kWh
EMISSION DATA EU	
Exhaust emissions (CO average)	278.5 g/kWh
Exhaust emissions (CO average)	804 g/kWh
Exhaust emissions (CO2 EU V)	804 g/kWh
Exhaust emissions (HC average)	41.7 g/kWh
Exhaust emissions (NOx average)	1.11 g/kWh
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	116 dB(A)
Sound power level, measured	114.34 dB(A)
Sound pressure (15m)	102 dB(A)
Sound pressure level at operators ear	102 dB(A)
VIBRATION	
Equivalent vibration level (ahv, eq) front handle	3.72 m/s ²
Equivalent vibration level (ahv, eq) rear handle	5.5 m/s ²