



Husqvarna 525RX Mark II

Husqvarna 525RX Mark II is a powerful, lightweight 25cc petrol brushcutter for professional use. Equipped with a large fuel tank for extended runtime. This robust, well-balanced brushcutter is designed for frequent trimming work. The large cutting width increases productivity. Connects easily to Husqvarna FleetServices with the connectivity device available as accessory. Comes with harness Balance 35, trimmer head and 4-tooth grass blade.



Intuitive controls

The choke and purge are easy to reach and understand.



Large fuel tank

The 0.65l fuel tank enables longer runtime. Improved productivity as fewer time-consuming stops for refueling are necessary.

Outstanding cutting capacity

'The Husqvarna X-Torq® engine combined with a market leading cutting diameter offers outstanding cutting capacity.



Connectivity ready

Dedicated space for Husqvarna connectivity device, which enables easy connection to digital services such as Husqvarna FleetServices.



FEATURES

- Cut more in less time
 - Longer runtime for improved productivity
 - Intuitive controls for easy operation
 - Compatible with digital services
 - Easier troubleshooting
 - High durability and decreased service costs
 - High hande bar, more leg space
 - For less tiresom work
 - Adjustable handlebar for best comfort
 - Offset handle bar for best comfort
- Powerful 50cc X-TORQ® engine reduces emissions by up to 60% and increases fuel efficiency by up to 20%
 - Less wear and service costs
 - Easy to service and maintain starter
 - Stop switch automatically resets to ON so trimmer is ready for next use
 - Air purge removes air from carburetor and fuel system for easy starting
 - Grass bevel gear for best cutting performance
 - Tap 'n' Go trimmer head is easy to use and refill
 - Versatile use with combi guard

Technical Specifications		
CAPACITY		
Clutch engagement speed (±120)		4000 rpm
Clutch engagement upper limit		4200 rpm
Idling speed		3000 rpm
Idling upper limit		3400 rpm
Maximum power speed		8500 rpm
Maximum rpm output shaft		8200 rpm
Power output		1 kW
Racing speed lower limit		9200 rpm
Torque, max.		1.2 Nm
Torque, max. at rpm		6000 rpm
DIMENSIONS		
Article gross weight		9500 g
Article net weight		6100 g
Cutting width		45 cm
Racing speed lower limit		9200 rpm
Tube diameter		24 mm
Tube length		1483 mm
Weight (excl. cutting equipment)		5.5 kg
ENGINE		
Cylinder bore		34 mm
Cylinder displacement		25.4 cm³
Cylinder stroke		28 mm
Electrode gap		0.55 mm
Gear ratio		19
Ignition module air gap		0.3 mm
Spark plug		Husqvarna HQT-2
EQUIPMENT		
Air filter type		Two-stage
Drive gear angle		30 °
Grass blade		Grass 255-4
Harness		Balance 35
Trimmer head		T35 M10
LUBRICANT		
Fuel consumption		600 g/kWh
Fuel tank volume		0.65 l
Lubricant type (Engine)		Husqvarna 2 stroke or equiv. at 50:1
Power/fuel type		Gasoline
MATERIALS		
Master pack: Paper + Cardboard		0 g
Metal total		0 g
Paper + Cardboard total		0 g
PE total		0 g
PET total		0 g
Plastic foil		0 g
Plastic rigid		0 g
Plastic total		0 g
PS/EPS/HIPS total		0 g
PACKAGING		
Quantity in Master pack		1
EMISSION DATA EU		
Exhaust emissions (CO average)		337.1 g/kWh
Exhaust emissions (CO average)		1141 g/kWh
Exhaust emissions (CO2 EU V)		1141 g/kWh
Exhaust emissions (HC average)		29.55 g/kWh
Exhaust emissions (NOx average)		0.31 g/kWh
SOUND AND NOISE		

Technical Specifications	
Sound power level, measured	106 dB(A)
Sound pressure level at operators ear	94 dB(A)
VIBRATION	
Daily Vibration Exposure (A8)	1.9 m/s ²
Daily Vibration Time (Time factor)	3.5 h
Equivalent vibration level (ahv, eq) left handle	2.8 m/s ²
Equivalent vibration level (ahv, eq) right handle	2.7 m/s ²