



## Husqvarna TC 112

Conveniently comfortable mowing for outstanding results. Effortlessly navigate narrow passages and cover large areas of lawn trouble-free. Enjoy a smooth sit-in experience with its ergonomically placed levers, intuitive side-by-side pedals and spring-assisted cutting deck. Cut more for longer with an optimised bagging capacity, store in less space thanks to a compact design and enjoy the possibilities with its tow hook and range of compatible attachments.



### Adjustable driver seat

Tool-less adjustment of seat position.



### Hour meter

Helps you having control over service and maintenance intervals.

### Dual headlights

Dual headlights at the front.



### Ergonomic driving position

Easy-access controls and plenty of leg room thanks to the adjustable seat. The spring assisted height adjustment cutting deck makes it easy to operate.



## FEATURES

- Dual headlights at the front.
- Helps you having control over service and maintenance intervals.
- Tool-less adjustment of seat position.
- Easy-access controls and plenty of leg room thanks to the adjustable seat. The spring assisted height adjustment cutting deck makes it easy to operate.
- The cutting deck is equipped with anti-scalp wheels, which reduce the risk of scalping when cutting uneven lawns.
- Compact design for effortless navigation in narrow passages and easy storage while not in use.
- Safe and convenient access to the mow in reverse functionality.
- Lever to engage the cutting deck.
- Fuel level window makes it easy to check the fuel level.
- Dual pedal drive for better drive control and easy, intuitive operation.
- Towing hook Included for multiple rear attachments.
- Controls levers on one side make it easier to get in and out of the seat.
- Large bag collects your grass clippings, leaving a clean lawn as a result.
- Turn key start
- Easy speed and direction control with pedal-operated hydrostatic transmission. Separate pedals for forward and reverse.
- Easy accessible cutting height adjustment for improved ergonomics. The spring-assisted cutting deck makes adjustment easier.

Technical Specifications	
<b>BATTERY</b>	
Battery capacity	20 Ah
Battery voltage	12 V
<b>CAPACITY</b>	
Net power at preset rpm	2800 rpm
Power output	8.0 kW
<b>DIMENSIONS</b>	
Article gross weight	238000 g
Article net weight	198000 g
Base machine, height	110 cm
Base machine, length	166.5 cm
Base machine, width	92 cm
Collector volume	200 l
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Lever, while seated
Cutting height steps	6
Cutting width	95 cm
Height	110 cm
Seat back height	Medium
Tyre dimensions, front	15x6-6
Tyre dimensions, rear	18x8.5-8
Weight	211 kg
Wheelbase	115 cm
<b>ENGINE</b>	
Cylinders	1
Cylinder displacement	413 cm <sup>3</sup>
Engine brand	Husqvarna
Engine cooling	Air
Engine name	HS 413AE
Fuel tank volume	6 l
Fuel tank volume	1.59 gal (US)
Generator	12 A
Motor/engine manufacturer	Husqvarna
Motor/engine model	HS 413AE
Transmission manufacturer	Hydro-Gear
Transmission model	T2
Transmission type	Hydrostatic
<b>EQUIPMENT</b>	
Air filter type	Cartridge with pre filter
Anti-scalp wheels	2
BioClip® kit	Available as accessory
Blade engagement	Manual
Blade type	Collect
Blades	2 pcs
Collector	Included
Cup holder	Yes
Cutting deck type	Stamped
Cutting methods	Collection/BioClip®/Rear discharge
Deck Wash Port	Yes
Deflector	Available as accessory
Drive method	Dual pedal-operation
Front-End Protection	Available as accessory
Generator	12 A
Greasable mandrels	No
Headlights	Yes
Hour meter type	Digital

Technical Specifications	
Mulching kit	Available as accessory
Powder-coated cutting deck	No
Seat type	Standard
<b>LUBRICANTS</b>	
Engine lubrication type	Pressure
Fuel consumption	441 g/kWh
Fuel tank location	Front
Oil capacity	1.15 l
Oil filter	No
Power/fuel type	Petrol
<b>MATERIALS</b>	
Cutting deck material	Steel
Master pack: Paper + Cardboard	0 g
Metal total	3820 g
Paper + Cardboard total	7410 g
PE total	285 g
PET total	0 g
Plastic foil	285 g
Plastic rigid	0 g
Plastic total	285 g
PS/EPS/HIPS total	0 g
Seat material	PU
<b>PACKAGING</b>	
Packaging height	850 mm
Packaging length	1700 mm
Packaging width	1135 mm
Quantity in Master pack	1
<b>SOUND AND NOISE</b>	
Sound power level, guaranteed (LWA)	97.2 dB(A)
Sound pressure level at operators ear	83 dB(A)
<b>VIBRATION</b>	
Vibration level seat	1.7 m/s <sup>2</sup>
Vibration level steering wheel	5.3 m/s <sup>2</sup>